

EUROPEAN PATENT OFFICE



Patent Abstracts of Japan

PUBLICATION NUMBER : 05064810
PUBLICATION DATE : 19-03-93


APPLICATION DATE : 10-09-91
APPLICATION NUMBER : 03230128

APPLICANT : POLYPLASTICS CO;

INVENTOR : KOBAYASHI NAOYUKI;

INT.CL. : B29B 15/12 B29B 11/16 C08J 5/04
C08K 7/02 D04H 1/42 // B29K105:10

TITLE : MANUFACTURE OF FIBER
REINFORCED COMPOSITE MATERIAL



ABSTRACT : PURPOSE: To obtain long fiber reinforced thermoplastic resin composition, in which no fuzz develops and the adherence between fiber and matrix is excellent, by a method wherein strand is pressed with rolls in the form of ribbon and, after that, shaped by being passed through a shaping nozzle.

CONSTITUTION: Continuous reinforcing fiber roving 2 is introduced in molten thermoplastic resin so as to infiltrate the molten resin in the fibers. Next, the resultant roving is continuously drawn out with a drawing device under the condition that excess resin is squeezed out by means of a nozzle. The resultant strand 3 is pressed with rolls 4 in the form of ribbon and, after that, shaped by being passed through a shaping nozzle 5 in order to strand-shaped fiber reinforced composite material.

COPYRIGHT: (C)1993,JPO&Japio



© PAJ / JPO

PN JP5064810 A 19930319

TI - MANUFACTURE OF FIBER REINFORCED COMPOSITE MATERIAL

AB - PURPOSE: To obtain long fiber reinforced thermoplastic resin composition, in which no fuzz develops and the adhesion between fiber and matrix is excellent, by a method wherein strand is pressed with rolls in the form of ribbon and, after shaped by being passed through a shaping nozzle.

- CONSTITUTION: Continuous reinforcing fiber roving 2 is introduced in molten thermoplastic resin so as to infiltrate the molten resin in the fibers. Next, the resultant roving is continuously drawn out with a drawing device under the condition that excess resin is squeezed out by means of a nozzle. The resultant strand 3 is pressed with rolls 4 in the form of ribbon and, after that, shaped by being passed through a shaping nozzle 5 in order to obtain strand-shaped fiber reinforced composite material.

I - B29B15/12 B29B11/16 C08J5/04 C08K7/02 D04H1/42

SI - B29K105/10

PA - POLYPLASTICS CO

IN - HIRAGORI GENICHI; others: 01

ABD - 19930715

ABV - 017377

GR - M1446

AP - JP19910230128 19910910